



Inductive Sensors Serie 30 - NAMUR EN 60947-5-6

Housing M 32 x 1.5

- Housing material: PA / PPO
- For use in areas with the risk of gas explosion, zone 0
- For use in areas with the risk of dust explosion, zone 20
- Sensing distance $S_n = 15 \text{ mm}$

Certificates:





DMT 03 ATEX E 048	IECEX BVS 07.0031
⊕ II 1G Ex ia IIC T1-T6 Ga	Ex ia IIC T1-T6 Ga
⊕ II 1D Ex ia IIIC T101°C Da	Ex ia IIIC T101°C Da

Technical data

Non-Flush mountable

Operating distance S_n	15 mm
Electrical version	2-wire DC
Output	NAMUR EN 60947-5-6
Type	IAS-30-35-N-M32-StEx
Art.-No.	IA 0098
Operating voltage (U_B)	5 - 15 V DC, $U_i = 15 \text{ V DC}$
Output current active surface free	> typ. 2 mA
Output current active surface covered	< typ. 1.5 mA
Self-inductance (L)	2 mH
Self-capacitance (C)	250 nF
Permitted residual ripple max.	5 %
Frequency of operating cycles max.	1 kHz
Permitted ambient temperature	-20...+90 °C
LED-display	Yellow
Degree of protection IEC 60529	IP 67
Connection cable	2 m PUR, 2 x 0.75 mm ²
Housing material	PA / PPO
Active surface	PA / PPO
Lid	PC (FDA 21 CFR 177.1580)



All specifications are subject to change without notice. (05/2013)