



## Inductive Sensors

### Series 10 - PNP

Housing  $\varnothing$  6,5 mm








- Housing material: Stainless steel VA
- Sensing distance  $S_n = 1,5$  mm

Certificado:



<b>Technical data</b>	Flush mountable
Operating distance $S_n$	1.5 mm
Electrical version	3-wire DC
Output	Normally open (NO)
<b>Type NPN</b>	
<b>Art.-No.</b>	
Connection diagram No.	
<b>Type PNP</b>	<b>IAS-10-6.5/15-S</b>
<b>Art.-No.</b>	<b>IA 0254</b>
Connection diagram No.	4
Operating voltage ( $U_B$ )	10...30 V DC
Output current max. ( $I_o$ )	200 mA
Voltage drop max. ( $U_d$ )	$\leq 2$ V
Permitted residual ripple max.	20 %
No-load current ( $I_o$ )	Typ. 10 mA
Frequency of operating cycles max.	5 kHz
Permitted ambient temperature	-25...+70 °C
LED-display	Yes
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67
Norm	EN 60 947-5-2
Connection cable	2 m, PVC, 3 x 0.14 mm <sup>2</sup>
Housing material	VA No. 1.4305
Active surface	PA / PPO
Lid	PUR

All specifications are subject to change without notice. (11/2011)



Made in Switzerland