



Capacitive Sensors

Series 80 - PNP

- Housing \varnothing 30 mm
- Housing material: Stainless steel VA
- Sensing distance 2...12 mm adjustable
- Very short housing

Certificate:



Technical data

Flush mountable

Operating distance S_n	10 mm
Operating distance min. / max. adjustable	2...12 mm
Electrical version	3-wire DC
Output	Normally open (NO)

Type NPN

Art.-No.

Connection diagram No.

Type PNP

KAS-80-30/10-S

Art.-No.

KA 0003

Connection diagram No.

4

Operating voltage (U_B)

10...35 V DC

Output current max. (I_o)

250 mA

Voltage drop max. (U_o)

≤ 2.0 V

Permitted residual ripple max.

10 %

No-load current (I_o)

< 15 mA

Frequency of operating cycles max.

50 Hz

Permitted ambient temperature

-25...+70 °C

LED-display

Yellow

Protective circuit

Built-in

Degree of protection IEC 60529

IP 67

Norm

EN 60947-5-2

Connection

3 m, PUR, 3 x 0.14 mm²

Housing material

VA No. 1.4305








Active surface

PTFE (FDA 21 CFR 177.1550)

Lid

-

All specifications are subject to change without notice. (21.01.2013)



Made in Germany