



Capacitive Sensors
Series 70 - NPN
Series 80 - PNP








- Housing M 18 x 1
- Housing material: PA / PPO
 - Sensing distance 1...10 mm adjustable

Certificate:



Technical data	Non-flush mountable	Non-flush mountable
Operating distance S_n	8 mm	8 mm
Operating distance min. / max. adjustable	1...10 mm	1...10 mm
Electrical version	3-wire DC	4-wire DC
Output	Normally open (NO)	Antivalent
Type NPN	KAS-70-A23-S-K-NL	KAS-70-A23-A-K-NL
Art.-No.	KA 0368	KA 0362
Connection diagram No.	1	3
Type PNP	KAS-80-A23-S-K-NL	KAS-80-A23-A-K-NL
Art.-No.	KA 0324	KA 0325
Connection diagram No.	4	6
Operating voltage (U_B)	12...30 V DC	12...30 V DC
Output current max. (I_o)	200 mA	2 x 200 mA
Voltage drop max. (U_d)	≤ 2.0 V	≤ 2.0 V
Permitted residual ripple max.	5 %	5 %
No-load current (I_o)	< 15 mA	< 15 mA
Frequency of operating cycles max.	50 Hz	50 Hz
Permitted ambient temperature	-25...+70 °C	-25...+70 °C
LED-display	Yellow	Yellow
Protective circuit	Built-in	Built-in
Degree of protection IEC 60529	IP 67	IP 67
Norm	EN 60947-5-2	EN 60947-5-2
Connection	2 m, PUR, 3 x 0.34 mm ²	2 m, PVC, 4 x 0.34 mm ²
Housing material	PA / PPO	PA / PPO
Active surface	PA / PPO	PA / PPO
Lid	PA / PPO	PA / PPO

All specifications are subject to change without notice. (09.03.2011)



Made in Germany