



Capacitive Sensors

Series 80 - PNP

Housing M 30 x 1.5

- Housing material: PPO
- Sensing distance 0.5...25 mm adjustable










Certificate:



Quattro^{ETC}Protect™

Technical data	Flush mountable
Operating distance S_n	10 mm
Operating distance min. / max. adjustable	0.5...25 mm
Electrical version	4-wire DC
Output	Antivalent (NO + NC)
Type NPN	
Art.-No.	
Connection diagram No.	
Type PNP	
Art.-No.	
Connection diagram No.	
KAS-80-A14/40-A-K	
KA 0835	
Connection diagram No.	
6	
Operating voltage (U_B)	10...35 V DC
Output current max. (I_o)	2 x 200 mA
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	200 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67
Norm	EN 60947-5-2
Connection cable	2 m, PUR, 4 x 0.14 mm ²
Housing material	PPO
Active surface	PPO
Lid	PA / PPO
Media optimized	Yes



Made in Germany

All specifications are subject to change without notice. (05.10.2011)